


- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: DIN 2215, RMA IP 20, ISO 4184, BS 3790, API 1 B, JIS K 6323
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Classical V-Belt

Section of Belt	Z	A
Top Width "T" (mm)	10	13
Height "H" (mm)	6	8
Belt Weight Kg/m	0.059	0.108



Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
Z18	480	19.5
Z19	510	20.5
Z20	530	21.5
Z21	560	22.5
Z22	580	23.5
Z23	610	24.5
Z24	640	25.5
Z25	660	26.5
Z26	690	27.5
Z27	710	28.5
Z28	740	29.5
Z29	760	30.5
Z30	790	31.5
Z31	810	32.5
Z32	840	33.5
Z33	860	34.5
Z34	890	35.5
Z35	910	36.5
Z36	940	37.5
Z37	970	38.5
Z38	990	39.5
Z39	1020	40.5
Z40	1040	41.5
Z41	1070	42.5
Z42	1090	43.5
Z43	1120	44.5
Z44	1140	45.5
Z45	1170	46.5
Z46	1190	47.5
Z47	1220	48.5
Z48	1240	49.5
Z49	1270	50.5
Z50	1300	51.5
Z51	1320	52.5
Z52	1350	53.5
Z53	1370	54.5
Z54	1400	55.5
Z55	1420	56.5
Z56	1450	57.5
Z57	1470	58.5
Z58	1500	59.5
Z59	1520	60.5
Z60	1550	61.5
Z61	1570	62.5
Z62	1600	63.5
Z63	1630	64.5
Z64	1650	65.5

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
Z65	1680	66.5
Z66	1700	67.5
Z67	1730	68.5
Z68	1750	69.5
Z69	1780	70.5
Z70	1800	71.5
Z71	1830	72.5
Z72	1850	73.5
Z73	1880	74.5
Z74	1910	75.5
Z75	1930	76.5
Z76	1960	77.5
Z77	1980	78.5
Z78	2010	79.5
Z79	2030	80.5
Z80	2060	81.5
Z81	2080	82.5
Z82	2110	83.5
Z83	2130	84.5
Z84	2160	85.5
Z85	2180	86.5

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
A18	490	20
A19	520	21
A20	540	22
A21	570	23
A22	590	24
A23	620	25
A24	640	26
A25	670	27
A26	690	28
A27	720	29
A28	740	30
A29	770	31
A30	800	32
A31	820	33
A32	850	34
A33	870	35
A34	900	36
A35	920	37
A36	950	38
A37	970	39
A38	1000	40
A39	1020	41
A40	1050	42
A41	1070	43
A42	1100	44
A43	1130	45
A44	1150	46
A45	1180	47
A46	1200	48
A47	1230	49
A48	1250	50
A49	1280	51
A50	1300	52
A51	1330	53
A52	1350	54
A53	1380	55
A54	1400	56
A55	1430	57
A56	1460	58
A57	1480	59
A58	1510	60
A59	1530	61
A60	1560	62
A61	1580	63
A62	1610	64
A63	1630	65
A64	1660	66


Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
A65	1680	67
A66	1710	68
A67	1730	69
A68	1760	70
A69	1790	71
A70	1810	72
A71	1840	73
A72	1860	74
A73	1890	75
A74	1910	76
A75	1940	77
A76	1960	78
A77	1990	79
A78	2010	80
A79	2040	81
A80	2070	82
A81	2090	83
A82	2120	84
A83	2140	85
A84	2170	86
A85	2190	87
A86	2220	88
A87	2240	89
A88	2270	90
A89	2290	91
A90	2320	92
A91	2340	93
A92	2370	94
A93	2400	95
A94	2420	96
A95	2450	97
A96	2470	98
A97	2500	99
A98	2520	100
A100	2570	102
A103	2650	105
A105	2700	107
A110	2830	112
A112	2880	114
A115	2950	117
A116	2980	118
A118	3030	120
A120	3080	122
A124	3180	126
A125	3210	127
A128	3280	130

"A" Section upto 180 Inches

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: DIN 2215, RMA IP 20, ISO 4184, BS 3790, API 1 B, JIS K 6323
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Classical V-Belt

Section of Belt	B	C
Top Width "T"(mm)	17	22
Height "H" (mm)	11	14
Belt Weight Kg/m	0.182	0.299



Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
B20	550	23
B21	580	24
B22	600	25
B23	630	26
B24	650	27
B25	680	28
B26	700	29
B27	730	30
B28	750	31
B29	780	32
B30	810	33
B31	830	34
B32	860	35
B33	880	36
B34	910	37
B35	930	38
B36	960	39
B37	980	40
B38	1010	41
B39	1030	42
B40	1060	43
B41	1080	44
B42	1110	45
B43	1140	46
B44	1160	47
B45	1190	48
B46	1210	49
B47	1240	50
B48	1260	51
B49	1290	52
B50	1310	53
B51	1340	54
B52	1360	55
B53	1390	56
B54	1410	57
B55	1440	58
B56	1470	59
B57	1490	60
B58	1520	61
B59	1540	62
B60	1570	63
B61	1590	64
B62	1620	65
B63	1640	66
B64	1670	67
B65	1690	68
B66	1720	69

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
B67	1740	70
B68	1770	71
B69	1800	72
B70	1820	73
B71	1850	74
B72	1870	75
B73	1900	76
B74	1920	77
B75	1950	78
B76	1970	79
B77	2000	80
B78	2020	81
B79	2050	82
B80	2080	83
B81	2100	84
B82	2130	85
B83	2150	86
B84	2180	87
B85	2200	88
B86	2230	89
B87	2250	90
B88	2280	91
B89	2300	92
B90	2330	93
B91	2350	94
B92	2380	95
B93	2410	96
B94	2430	97
B95	2460	98
B96	2480	99
B97	2510	100
B98	2530	101
B99	2560	102
B100	2580	103
B102	2630	105
B103	2660	106
B104	2680	107
B105	2710	108
B106	2740	109
B108	2790	111
B110	2840	113
B112	2890	115
B114	2940	117
B115	2960	118
B116	2990	119
B118	3040	121
B120	3090	123

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
B121	3110	124
B122	3140	125
B124	3190	127
B126	3240	129
B128	3290	131
B130	3350	133
B133	3420	136
B136	3500	139
B138	3550	141
B140	3600	143
B142	3650	145
B144	3700	147
B146	3750	149
B148	3800	151
B150	3850	153
B152	3900	155
B154	3950	157
B158	4060	161
B162	4160	165
B166	4260	169
B173	4440	176
B180	4620	183
B188	4820	191
B190	4870	193
B195	5000	198
B205	5250	208
B210	5380	213
B225	5760	228
B240	6140	243
B255	6520	258
B270	6900	273
B285	7280	288
B300	7660	303
B315	8040	318


"B" section upto 570 inches

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
C36	970	40
C37	1000	41
C38	1020	42
C39	1050	43
C40	1070	44
C41	1100	45
C42	1120	46
C43	1150	47
C44	1170	48
C45	1200	49
C46	1220	50
C47	1250	51
C48	1280	52
C50	1330	54
C51	1350	55
C53	1400	57
C54	1430	58
C55	1450	59
C57	1500	61
C60	1580	64
C62	1630	66
C63	1660	67
C65	1710	69
C67	1760	71
C68	1780	72
C69	1810	73
C70	1830	74
C71	1860	75
C72	1880	76
C73	1910	77
C75	1960	79
C76	1990	80
C78	2040	82
C80	2090	84
C81	2110	85
C83	2160	87
C84	2190	88
C85	2220	89
C87	2270	91
C90	2340	94
C92	2390	96
C93	2420	97
C95	2470	99
C96	2490	100
C97	2520	101
C99	2570	103
C100	2600	104

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: DIN 2215, RMA IP 20, ISO 4184, BS 3790, API 1 B, JIS K 6323
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Classical V-Belt

Section of Belt	C	D	E
Top Width "T"(mm)	22	32	38
Height "H" (mm)	14	19	23
Belt Weight Kg/m	0.299	0.608	0.907



Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
C101	2620	105
C103	2670	107
C105	2720	109
C106	2750	110
C107	2770	111
C108	2800	112
C109	2820	113
C110	2850	114
C111	2880	115
C112	2900	116
C115	2980	119
C116	3000	120
C118	3050	122
C120	3100	124
C122	3150	126
C124	3210	128
C126	3260	130
C128	3310	132
C130	3360	134
C136	3510	140
C140	3610	144
C144	3710	148
C148	3820	152
C150	3870	154
C152	3920	156
C156	4020	160
C158	4070	162
C162	4170	166
C170	4370	174
C173	4450	177
C180	4630	184
C185	4760	189
C190	4880	194
C195	5010	199
C210	5390	214
C225	5770	229
C238	6100	242
C240	6150	244
C255	6530	259
C268	6860	272
C270	6910	274
C285	7300	289
C298	7630	302
C300	7680	304
C315	8060	319
C328	8390	332
C330	8440	334

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
C345	8820	349
C358	9150	362
C360	9200	364
C390	9960	394
C418	10670	422
C420	10720	424

"C" section upto 598 inches


Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
D75	1990	80
D88	2320	93
D90	2370	95
D95	2500	100
D105	2750	110
D112	2930	117
D120	3130	125
D128	3330	133
D136	3540	141
D144	3740	149
D158	4100	163
D162	4200	167
D173	4480	178
D180	4660	185
D195	5040	200
D204	5260	209
D210	5420	215
D225	5800	230
D238	6130	243
D240	6180	245
D255	6560	260
D268	6890	273
D270	6940	275
D285	7320	290
D298	7650	303
D300	7700	305
D314	8060	319
D315	8080	320
D328	8410	333
D330	8470	335
D345	8850	350
D358	9180	363
D360	9230	365
D390	9990	395
D418	10700	423
D420	10750	425
D441	11280	446
D450	11510	455
D478	12220	483
D480	12280	485
D538	13750	543
D540	13800	545
D598	15270	603
D600	15320	605

Size	Pitch Length in MM (Lp)	Outside Length in Inch (La)
E180	4670	186
E195	5050	201
E210	5430	216
E238	6140	244
E240	6190	246
E268	6900	274
E270	6950	276
E298	7660	304
E300	7720	306
E328	8430	334
E330	8480	336
E358	9190	364
E360	9240	366
E390	10000	396
E394	10100	400
E418	10710	424
E420	10760	426
E441	11300	447
E478	12240	484
E480	12290	486
E538	13760	544
E540	13810	546
E550	14065	556
E598	15280	604

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: DIN 2215, RMA IP 20, ISO 4184, BS 3790, API 1 B, JIS K 6323
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Wedge V-Belt

Section of Belt	SPZ	SPA
Top Width "T"(mm)	10	13
Height "H" (mm)	8	10
Belt Weight Kg/m	0.079	0.125



Size	Pitch Length in MM (Lp)
SPZ604	604
SPZ612	612
SPZ630	630
SPZ637	637
SPZ640	640
SPZ660	660
SPZ672	672
SPZ680	680
SPZ682	682
SPZ710	710
SPZ722	722
SPZ730	730
SPZ737	737
SPZ750	750
SPZ758	758
SPZ762	762
SPZ787	787
SPZ800	800
SPZ812	812
SPZ825	825
SPZ837	837
SPZ850	850
SPZ862	862
SPZ875	875
SPZ887	887
SPZ900	900
SPZ912	912
SPZ925	925
SPZ937	937
SPZ950	950
SPZ962	962
SPZ987	987
SPZ1000	1000
SPZ1010	1010
SPZ1012	1012
SPZ1024	1024
SPZ1037	1037
SPZ1047	1047
SPZ1060	1060
SPZ1077	1077
SPZ1080	1080
SPZ1087	1087
SPZ1112	1112
SPZ1120	1120
SPZ1137	1137
SPZ1140	1140
SPZ1150	1150

Size	Pitch Length in MM (Lp)
SPZ1162	1162
SPZ1150	1150
SPZ1187	1187
SPZ1202	1202
SPZ1210	1210
SPZ1212	1212
SPZ1227	1227
SPZ1237	1237
SPZ1250	1250
SPZ1262	1262
SPZ1270	1270
SPZ1287	1287
SPZ1312	1312
SPZ1320	1320
SPZ1337	1337
SPZ1340	1340
SPZ1362	1362
SPZ1387	1387
SPZ1400	1400
SPZ1412	1412
SPZ1420	1420
SPZ1430	1430
SPZ1437	1437
SPZ1450	1450
SPZ1462	1462
SPZ1470	1470
SPZ1487	1487
SPZ1500	1500
SPZ1512	1512
SPZ1520	1520
SPZ1527	1527
SPZ1537	1537
SPZ1560	1560
SPZ1562	1562
SPZ1587	1587
SPZ1600	1600
SPZ1612	1612
SPZ1637	1637
SPZ1650	1650
SPZ1662	1662
SPZ1687	1687
SPZ1700	1700
SPZ1712	1712
SPZ1737	1737
SPZ1750	1750
SPZ1762	1762
SPZ1787	1787

Size	Pitch Length in MM (Lp)
SPZ1800	1800
SPZ1812	1812
SPZ1837	1837
SPZ1850	1850
SPZ1862	1862
SPZ1887	1887
SPZ1900	1900
SPZ1937	1937
SPZ1950	1950
SPZ1962	1962
SPZ1987	1987
SPZ2000	2000
SPZ2030	2030
SPZ2037	2037
SPZ2062	2062
SPZ2087	2087
SPZ2120	2120
SPZ2137	2137
SPZ2187	2187
SPZ2240	2240
SPZ2280	2280
SPZ2287	2287
SPZ2300	2300
SPZ2360	2360
SPZ2410	2410
SPZ2437	2437
SPZ2487	2487
SPZ2500	2500
SPZ2540	2540
SPZ2650	2650
SPZ2800	2800
SPZ2840	2840
SPZ3000	3000
SPZ3150	3150
SPZ3350	3350
SPZ3550	3550

SPZ Range upto 4000 MM


Size	Pitch Length in MM (Lp)
SPA630	630
SPA670	670
SPA730	730
SPA732	732
SPA750	750
SPA760	760
SPA762	762
SPA772	772
SPA782	782
SPA800	800
SPA820	820
SPA832	832
SPA850	850
SPA900	900
SPA910	910
SPA922	922
SPA932	932
SPA950	950
SPA967	967
SPA982	982
SPA1000	1000
SPA1032	1032
SPA1060	1060
SPA1082	1082
SPA1107	1107
SPA1120	1120
SPA1132	1132
SPA1150	1150
SPA1157	1157
SPA1180	1180
SPA1207	1207
SPA1232	1232
SPA1250	1250
SPA1257	1257
SPA1272	1272
SPA1282	1282
SPA1300	1300
SPA1307	1307
SPA1320	1320
SPA1332	1332
SPA1340	1340
SPA1357	1357
SPA1360	1360
SPA1375	1375
SPA1382	1382
SPA1400	1400
SPA1407	1407

Size	Pitch Length in MM (Lp)
SPA1425	1425
SPA1430	1430
SPA1432	1432
SPA1450	1450
SPA1457	1457
SPA1482	1482
SPA1500	1500
SPA1507	1507
SPA1525	1525
SPA1532	1532
SPA1550	1550
SPA1557	1557
SPA1582	1582
SPA1600	1600
SPA1607	1607
SPA1630	1630
SPA1632	1632
SPA1650	1650
SPA1657	1657
SPA1662	1662
SPA1675	1675
SPA1680	1680
SPA1682	1682
SPA1700	1700
SPA1707	1707
SPA1732	1732
SPA1750	1750
SPA1757	1757
SPA1782	1782
SPA1800	1800
SPA1807	1807
SPA1832	1832
SPA1850	1850
SPA1857	1857
SPA1882	1882
SPA1900	1900
SPA1907	1907
SPA1932	1932
SPA1950	1950
SPA1982	1982
SPA2000	2000
SPA2032	2032
SPA2057	2057
SPA2082	2082
SPA2120	2120
SPA2132	2132
SPA2182	2182

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: DIN 2215, RMA IP 20, ISO 4184, BS 3790, API 1 B, JIS K 6323
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Wedge V-Belt

Section of Belt	SPA	SPB	SPC
Top Width "T"(mm)	13	17	22
Height "H" (mm)	10	13	18
Belt Weight Kg/m	0.125	0.181	0.348



Size	Pitch Length in MM (Lp)
SPA2207	2207
SPA2227	2227
SPA2232	2232
SPA2240	2240
SPA2282	2282
SPA2300	2300
SPA2307	2307
SPA2332	2332
SPA2360	2360
SPA2382	2382
SPA2432	2432
SPA2482	2482
SPA2500	2500
SPA2532	2532
SPA2582	2582
SPA2607	2607
SPA2650	2650
SPA2682	2682
SPA2732	2732
SPA2782	2782
SPA2800	2800
SPA2832	2832
SPA2882	2882
SPA2982	2982
SPA3000	3000
SPA3070	3070
SPA3082	3082
SPA3150	3150
SPA3182	3182
SPA3282	3282
SPA3350	3350
SPA3482	3482
SPA3550	3550
SPA3750	3750
SPA4000	4000
SPA4250	4250
SPA4500	4500

Size	Pitch Length in MM (Lp)
SPB1250	1250
SPB1260	1260
SPB1320	1320
SPB1340	1340
SPB1400	1400
SPB1410	1410
SPB1450	1450
SPB1500	1500
SPB1510	1510
SPB1590	1590
SPB1600	1600
SPB1627	1627
SPB1690	1690
SPB1700	1700
SPB1800	1800
SPB1900	1900
SPB2000	2000
SPB2020	2020
SPB2098	2098
SPB2120	2120
SPB2150	2150
SPB2180	2180
SPB2240	2240
SPB2280	2280
SPB2300	2300
SPB2360	2360
SPB2361	2361
SPB2410	2410
SPB2500	2500
SPB2530	2530
SPB2650	2650
SPB2680	2680
SPB2800	2800
SPB1990	1990
SPB3000	3000
SPB3150	3150
SPB3350	3350
SPB3550	3550
SPB3750	3750
SPB3800	3800
SPB4000	4000
SPB4150	4150
SPB4500	4500
SPB4750	4750
SPB5000	5000
SPB5300	5300
SPB5600	5600

Size	Pitch Length in MM (Lp)
SPB6000	6000
SPB6700	6700
SPB7100	7100
SPB7500	7500
SPB8000	8000

SPB Range Upto 14500 MM


Size	Pitch Length in MM (Lp)
SPC1800	1800
SPC2000	2000
SPC2120	2120
SPC2240	2240
SPC2360	2360
SPC2500	2500
SPC2650	2650
SPC2800	2800
SPC3000	3000
SPC3150	3150
SPC3350	3350
SPC3550	3550
SPC3750	3750
SPC4000	4000
SPC4250	4250
SPC4500	4500
SPC4750	4750
SPC5000	5000
SPC5300	5300
SPC5600	5600
SPC6000	6000
SPC6300	6300
SPC6700	6700
SPC7100	7100
SPC7500	7500
SPC8000	8000
SPC8500	8500
SPC9000	9000
SPC10000	10000
SPC10600	10600
SPC11300	11300
SPC11600	11600
SPC12500	12500

SPC Range Upto 14500 MM

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: RMA IP 22, API 1 B
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Narrow V-Belt

Section of Belt	3V	5V	8V
Top Width "T" (mm)	10	17	25
Height "H" (mm)	8	14	23
Belt Weight Kg/m	0.079	0.181	0.561



Size	Outside Length-Inches (La)
3V250	25.0
3V265	26.5
3V280	28.0
3V300	30.0
3V315	31.5
3V135	13.5
3V355	35.5
3V175	17.5
3V400	40.0
3V425	42.5
3V450	45.0
3V475	47.5
3V500	50.0
3V510	51.0
3V560	56.0
3V600	60.0
3V630	63.0
3V670	67.0
3V710	71.0
3V750	75.0
3V800	80.0
3V850	85.0
3V900	90.0
3V950	95.0
3V1000	100.0
3V1060	106.0
3V1120	112.0
3V1180	118.0
3V1250	125.0
3V1320	132.0
3V1400	140.0

Size	Outside Length-Inches (La)
5V500	50.0
5V560	56.0
5V600	60.0
5V630	63.0
5V670	67.0
5V710	71.0
5V750	75.0
5V800	80.0
5V850	85.0
5V900	90.0
5V950	95.0
5V1000	100.0
5V1060	106.0
5V1120	112.0
5V1180	118.0
5V1250	125.0
5V1320	132.0
5V1500	150.0
5V1600	160.0
5V1700	170.0
5V1800	180.0
5V1900	190.0
5V2000	200.0
5V2120	212.0
5V2240	224.0
5V2360	236.0
5V2500	250.0
5V2650	265.0
5V2800	280.0
5V3000	300.0
5V3150	315.0
5V3350	335.0
5V3550	355.0


"5V" Range upto
570 Inches - La

Size	Outside Length-Inches (La)
8V1000	100.0
8V1120	112.0
8V1180	118.0
8V1250	125.0
8V1310	131.0
8V1400	140.0
8V1500	150.0
8V1600	160.0
8V1700	170.0
8V1800	180.0
8V1900	190.0
8V2000	200.0
8V2120	212.0
8V2240	224.0
8V2360	236.0
8V2500	250.0
8V2650	265.0
8V2800	280.0
8V3000	300.0
8V3150	315.0
8V3350	335.0
8V3550	355.0
8V3750	375.0
8V4000	400.0
8V4250	425.0
8V4500	450.0
8V4750	475.0
8V5000	500.0
8V5600	560.0
8V5800	580.0

8V- Regular
8V- HP (High Power) For Extreme Condition

5V- Regular
5V- HP (High Power) For Extreme Condition

Type: Banded V-Belt



Section	Size Range	Size Range
A	42-150	6
B	42-173	6
B	174-598	5
C	62-120	4
C	121-598	5
3V	420-1500	6
5V	950-1750	6
5V	1760-5980	5
8V	1000-5980	5
SPZ	1100-3100	8
SPA	1100-3100	8
SPB	1100-3100	6
SPC	2280-3100	6
SPC	3150-10600	5
AX	42-122	8
BX	42-122	6
CX	42-122	6
SPZX	1100-3100	8
SPAX	1100-3100	8
SPBX	1100-3100	6
SPCX	1100-3100	6
3VX	470-4200	8
5VX	470-4200	6

Type: Raw Edge Cogged (REC) V-Belt




Cogged belt are cut type / toothed belt, denoted by "X" in the belt size
For Belt Dimension & Range - refer respective size of Classical V-Belt, Wedge Belt & Narrow V-Belt
Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value
REC Belts are manufactured from specially heat treated and High Modulus-Low Stretch polyester cord

Section of Belt	AX	BX	CX	SPZX / XPZ	SPAX / XPA	SPBX / XPB	SPCX / XPC	3VX	5VX
Belt Weight Kg/m	0.079	0.181	0.561	0.073	0.123	0.173	0.29	0.073	0.173

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: RMA IP 26, SAE J 1459, ISO 9981, JASO E 109
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Multi Rib / Serpentine Belt

Cross Section		PH	PJ	PL	PM
Pitch (p)	mm	1.6	2.34	4.7	9.4
Height (t)	mm	2.9	3.8	7	13.5
Belt Wt Kg/Rib mtr		0.006	0.01	0.037	0.12
Nominal Length (Angle 40 Degree)	mm	1320 - 2540	450 - 2500	1250 - 15000	2300 - 15000
	Inches	50 - 100	18 - 100	49 - 590	90 - 590



PH Section-Max Rib 24

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
520 H	52.0	1321
530 H	53.0	1346
540 H	54.0	1372
550 H	55.0	1397
560 H	56.0	1422
580 H	58.0	1473
610 H	61.0	1549
625 H	62.5	1588
655 H	65.5	1664
690 H	69.0	1753
730 H	73.0	1854
745 H	74.5	1892
750 H	75.0	1905
760 H	76.0	1930
770 H	77.0	1956
775 H	77.5	1969
780 H	78.0	1981
785 H	78.5	1994
790 H	79.0	2007
800 H	80.0	2032
810 H	81.0	2057
820 H	82.0	2083
830 H	83.0	2108
840 H	84.0	2134
850 H	85.0	2159
860 H	86.0	2184
870 H	87.0	2210
880 H	88.0	2235
890 H	89.0	2261
900 H	90.0	2286
910 H	91.0	2311
920 H	92.0	2337
930 H	93.0	2362
940 H	94.0	2388
950 H	95.0	2413
960 H	96.0	2438
970 H	97.0	2464
980 H	98.0	2489
990 H	99.0	2515
1000 H	100.0	2540

PJ Section-Max Rib 24

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
190 J	19.0	483
200 J	20.0	508
220 J	22.0	559
230 J	23.0	584
240 J	24.0	610
260 J	26.0	660
280 J	28.0	711
285 J	28.5	724
300 J	30.0	762
320 J	32.0	813
340 J	34.0	864
360 J	36.0	914
370 J	37.0	940
380 J	38.0	965
400 J	40.0	1016
415 J	41.5	1054
430 J	43.0	1092
435 J	43.5	1105
440 J	44.0	1118
445 J	44.5	1130
450 J	45.0	1143
460 J	46.0	1168
470 J	47.0	1194
480 J	48.0	1219
485 J	48.5	1232
490 J	49.0	1245
500 J	50.0	1270
505 J	50.5	1283
510 J	51.0	1295
515 J	51.5	1308
520 J	52.0	1321
530 J	53.0	1346
540 J	54.0	1372
550 J	55.0	1397
560 J	56.0	1422
580 J	58.0	1473
610 J	61.0	1549
625 J	62.5	1588
650 J	65.0	1651
655 J	65.5	1664
690 J	69.0	1753
730 J	73.0	1854
745 J	74.5	1892
750 J	75.0	1905

PJ Section-Max Rib 24

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
770 J	77.0	1956
775 J	77.5	1969
785 J	78.5	1994
820 J	82.0	2083
870 J	87.0	2210
890 J	89.0	2261
900 J	90.0	2286
920 J	92.0	2337
940 J	94.0	2388
960 J	96.0	2438
980 J	98.0	2489
1000 J	100.0	2540

PL Section-Max Rib 50

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
500 L	50.0	1270
525 L	52.5	1334
540 L	54.0	1372
550 L	55.0	1397
560 L	56.0	1422
580 L	58.0	1473
615 L	61.5	1562
635 L	63.5	1613
655 L	65.5	1664
675 L	67.5	1715
710 L	71.0	1803
725 L	72.5	1842
765 L	76.5	1943
780 L	78.0	1981
795 L	79.5	2019
815 L	81.5	2070
825 L	82.5	2096
840 L	84.0	2134
865 L	86.5	2197
880 L	88.0	2235
915 L	91.5	2324
930 L	93.0	2362
975 L	97.5	2477
990 L	99.0	2515
1065 L	106.5	2705
1080 L	108.0	2743
1120 L	112.0	2845

PL Section-Cont/..

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
1140 L	114.0	2896
1150 L	115.0	2921
1180 L	118.0	2997
1215 L	121.5	3086
1230 L	123.0	3124
1295 L	129.5	3289
1310 L	131.0	3327
1375 L	137.5	3493
1455 L	145.5	3696
1595 L	159.5	4051
1650 L	165.0	4191
1760 L	176.0	4470
1820 L	182.0	4623
1980 L	198.0	5029
2120 L	212.0	5385
2400 L	240.0	6096
2410 L	241.0	6121
2710 L	271.0	6883
3010 L	301.0	7645




PM Section-Max Rib 36

Size	Effect Length-Inches (Le)	Effect Length-MM (Le)
990 M	99.0	2515
1060 M	106.0	2692
1115 M	111.5	2832
1150 M	115.0	2921
1185 M	118.5	3010
1230 M	123.0	3124
1310 M	131.0	3327
1390 M	139.0	3531
1470 M	147.0	3734
1610 M	161.0	4089
1650 M	165.0	4191
1760 M	176.0	4470
1830 M	183.0	4648
1980 M	198.0	5029
2130 M	213.0	5410
2410 M	241.0	6121
2710 M	271.0	6883
3010 M	301.0	7645
3310 M	331.0	8407
3610 M	361.0	9169

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: RMA IP 24
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Timing Belt

Cross Section		XL	L	H
Pitch (p)	mm	5.08 - 1/5"	9.525 - 3/8"	12.7 - 1/2"
Height (t)	mm	2.30	3.60	4.30



Section XL

Length Code	Pitch Length-Inches	No. of Teeth
60XL	6.0	30
70XL	7.0	35
76XL	7.6	38
80XL	8.0	40
90XL	9.0	45
96XL	9.6	48
100XL	10.0	50
102XL	10.2	51
106XL	10.6	53
108XL	10.8	54
110XL	11.0	55
112XL	11.2	56
114XL	11.4	57
116XL	11.6	58
118XL	11.8	59
120XL	12.0	60
124XL	12.4	62
126XL	12.6	63
130XL	13.0	65
132XL	13.2	66
136XL	13.6	68
140XL	14.0	70
146XL	14.6	73
150XL	15.0	75
154XL	15.4	77
160XL	16.0	80
166XL	16.6	83
170XL	17.0	85
172XL	17.2	86
176XL	17.6	88
180XL	18.0	90
182XL	18.2	91
184XL	18.4	92
188XL	18.8	94
190XL	19.0	95
196XL	19.6	98
198XL	19.8	99
200XL	20.0	100
212XL	21.2	106
220XL	22.0	110
234XL	23.4	117
240XL	24.0	120
248XL	24.8	124
250XL	25.0	125

Section XL


Length Code	Pitch Length-Inches	No. of Teeth
260XL	26.0	130
270XL	27.0	135
276XL	27.6	138
280XL	28.0	140
286XL	28.6	143
290XL	29.0	145
300XL	30.0	150
316XL	31.6	158
320XL	32.0	160
330XL	33.0	165
340XL	34.0	170
344XL	34.4	172
352XL	35.2	176
380XL	38.0	190
384XL	38.4	192
390XL	39.0	195
400XL	40.0	200
412XL	41.2	206
414XL	41.4	207
432XL	43.2	216
450XL	45.0	225
460XL	46.0	230
490XL	49.0	245
564XL	56.4	282
574XL	57.4	287
580XL	58.0	290
612XL	61.2	306
630XL	63.0	315
Standard Width		
Code 025	1/4"	
Code 031	5/16"	
Code 037	3/8"	
Code 050	1/2"	
Code 075	3/4"	
Standards: RMA IP 24		

Section L

Length Code	Pitch Length-Inches	No. of Teeth
124L	12.4	33
130L	13.0	35
135L	13.5	36
143L	14.3	38
150L	15.0	40
177L	17.7	47
180L	18.0	48
185L	18.5	49
210L	21.0	56
240L	24.0	64
244L	24.4	65
255L	25.5	68
263L	26.3	70
265L	26.5	71
270L	27.0	72
275L	27.5	73
285L	28.5	76
300L	30.0	80
320L	32.0	85
330L	33.0	88
334L	33.4	89
345L	34.5	92
360L	36.0	96
375L	37.5	100
382L	38.2	102
405L	40.5	108
420L	42.0	112
450L	45.0	120
453L	45.3	121
465L	46.5	124
480L	48.0	128
495L	49.5	132
510L	51.0	136
525L	52.5	140
540L	54.0	144
585L	58.5	156
600L	60.0	160
619L	61.9	165
630L	63.0	168
634L	63.4	169
660L	66.0	176
Code 050	1/2"	Code 150 1 1/2"
Code 075	3/4"	Code 200 2"
Code 100	1"	

Section H




Length Code	Pitch Length-Inches	No. of Teeth
240H	24.0	48
250H	25.0	50
260H	26.0	52
270H	27.0	54
280H	28.0	56
285H	28.5	57
290H	29.0	58
300H	30.0	60
330H	33.0	66
350H	35.0	70
355H	35.5	71
360H	36.0	72
365H	36.5	73
375H	37.5	75
380H	38.0	76
390H	39.0	78
395H	39.5	79
400H	40.0	80
440H	44.0	88
445H	44.5	89
450H	45.0	90
460H	46.0	92
480H	48.0	96
485H	48.5	97
490H	49.0	98
500H	50.0	100
550H	55.0	110
560H	56.0	112
565H	56.5	113
570H	57.0	114
580H	58.0	116
585H	58.5	117
590H	59.0	118
600H	60.0	120
650H	65.0	130
660H	66.0	132
670H	67.0	134
680H	68.0	136
700H	70.0	140
750H	75.0	150
770H	77.0	154
780H	78.0	156
800H	80.0	160
850H	85.0	170



- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: RMA IP 24
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Timing Belt

Cross Section		H	XH	3M	5M
Pitch (p)	mm	12.7 - 1/2"	22.225 - 7/8"	3mm	5mm
Height (t)	mm	4.30	11.20	2.40	3.80



Section H Cont./.

Length Code	Pitch Length-Inches	No. of Teeth
900H	90.0	180
985H	98.5	197
1000H	100.0	200
1020H	102.0	204
1050H	105.0	210
1120H	112.0	224
1130H	113.0	226
1200H	120.0	240
1250H	125.0	250
1400H	140.0	280
1440H	144.0	288
1450H	145.0	290
1510H	151.0	302
1660H	166.0	332
1700H	170.0	340
1855H	185.5	371
Standard Width		
Code 075	3/4"	
Code 100	1"	
Code 150	1 1/2"	
Code 200	2"	
Code 300	3"	
Standards: RMA IP 24		

Section XH

Length Code	Pitch Length-Inches	No. of Teeth
508XH	50.8	58
560XH	56.0	64
630XH	63.0	72
700XH	70.0	80
770XH	77.0	88
800XH	80.0	91
805XH	80.5	92
840XH	84.0	96
850XH	85.0	97
980XH	98.0	112
1000XH	100.0	114
1120XH	112.0	128
1260XH	126.0	144
1400XH	140.0	160
1540XH	154.0	176
1575XH	157.0	180
1750XH	175.0	200
Standard Width		
Code 200	2"	
Code 300	3"	
Code 400	4"	
Code 500	5"	
Standards: RMA IP 24		

Section 3M

Length Code	Pitch Length-Inches	No. of Teeth
102-3M	102	34
111-3M	111	37
117-3M	117	39
120-3M	120	40
141-3M	141	47
150-3M	150	50
159-3M	159	53
168-3M	168	56
177-3M	177	59
180-3M	180	60
186-3M	186	62
192-3M	192	64
204-3M	204	68
207-3M	207	69
210-3M	210	70
213-3M	213	71
222-3M	222	74
225-3M	225	75
228-3M	228	76
234-3M	234	78
237-3M	237	79
240-3M	240	80
246-3M	246	82
270-3M	270	90
276-3M	276	92
282-3M	282	94
285-3M	285	95
306-3M	306	102
309-3M	309	103
312-3M	312	104
318-3M	318	106
324-3M	324	108
345-3M	345	115
348-3M	348	116
357-3M	357	119
360-3M	360	120
363-3M	363	121
366-3M	366	122
375-3M	375	125
384-3M	384	128
390-3M	390	130
423-3M	423	141
426-3M	426	142
447-3M	447	149

Section 5M

Length Code	Pitch Length-Inches	No. of Teeth
200-5M	200	40
225-5M	225	45
280-5M	280	56
285-5M	285	57
295-5M	295	59
300-5M	300	60
305-5M	305	61
310-5M	310	62
320-5M	320	64
325-5M	325	65
330-5M	330	66
365-5M	365	73
370-5M	370	74
375-5M	375	75
385-5M	385	77
395-5M	395	79
400-5M	400	80
440-5M	440	88
445-5M	445	89
450-5M	450	90
460-5M	460	92
470-5M	470	94
505-5M	505	101
520-5M	520	104
525-5M	525	105
560-5M	560	112
565-5M	565	113
570-5M	570	114
575-5M	575	115
615-5M	615	123
620-5M	620	124
625-5M	625	125
630-5M	630	126
635-5M	635	127
640-5M	640	128
645-5M	645	129
650-5M	650	130
695-5M	695	139
700-5M	700	140
710-5M	710	142
715-5M	715	143
725-5M	725	145
740-5M	740	148
790-5M	790	158

Section 3M Cont./.

Length Code	Pitch Length-Inches	No. of Teeth
459-3M	459	153
471-3M	471	157
474-3M	474	158
477-3M	477	159
492-3M	492	164
495-3M	495	165
SOI-3M	501	167
510-3M	510	170
513-3M	513	171
564-3M	564	188
570-3M	570	190
576-3M	576	192
579-3M	579	193
582-3M	582	194
582-3M	582	194



Section 3M Cont./.

Length Code	Pitch Length-Inches	No. of Teeth
597-3M	597	199
633-3M	633	211
639-3M	639	213
648-3M	648	216
654-3M	654	218
669-3M	669	223
675-3M	675	225
684-3M	684	228
699-3M	699	233
720-3M	720	240
750-3M	750	250
753-3M	753	251
801-3M	801	267
804-3M	804	268
Std Wid 6,9,15,20,30mm		

- * All F&F Fenner Belts are Heat and Oil resistant, Antistatic; Manufactured by Fenner (I) Ltd.
- * All F&F Belts are Pre-Heat & Stabilised hence does not require matching set
- * Standards: RMA IP 24
- * Sizes not mentioned in this catalogue can be supplied on request, Belt weight mentioned is approx. value

Type: Timing Belt

Cross Section		5M	8M	14M
Pitch (p)	mm	5mm	8mm	14mm
Height (t)	mm	3.80	6.00	10.00



Section 5M Cont'..

Length Code	Pitch Length-Inches	No. of Teeth
800-5M	800	160
810-5M	810	162
825-5M	825	165
830-5M	830	166
835-5M	835	167
850-5M	850	170
860-5M	860	172
870-5M	870	174
960-5M	960	192
975-5M	975	195
980-5M	980	196
1000-5M	1000	200
1025-5M	1025	205
1050-5M	1050	210
1100-5M	1100	220
1225-5M	1225	245
1270-5M	1270	254
1290-5M	1290	258
1350-5M	1350	270
1375-5M	1375	275
1400-5M	1400	280
1420-5M	1420	284
1455-5M	1455	291
1500-5M	1500	300
1945-5M	1945	389
2000-5M	2000	400
2050-5M	2050	410
2160-5M	2160	432
2250-5M	2250	450
2370-5M	2370	474
2460-5M	2460	492
2525-5M	2525	505

Std Wid 9,15,20,25,30mm

Section 8M

Length Code	Pitch Length-Inches	No. of Teeth
288-8M	288	36
384-8M	384	48
400-8M	400	50
408-8M	408	51
416-8M	416	52
512-8M	512	64
520-8M	520	65
536-8M	536	67
560-8M	560	70
568-8M	568	71
640-8M	640	80
656-8M	656	82
680-8M	680	85
688-8M	688	86
696-8M	696	87
712-8M	712	89
720-8M	720	90
728-8M	728	91
760-8M	760	95
776-8M	776	97
800-8M	800	100
816-8M	816	102
824-8M	824	103
840-8M	840	105
856-8M	856	107
864-8M	864	108
872-8M	872	109
880-8M	880	110
896-8M	896	112
920-8M	920	115
928-8M	928	116
944-8M	944	118
952-8M	952	119
1000-8M	1000	125
1016-8M	1016	127
1040-8M	1040	130
1056-8M	1056	132
1080-8M	1080	135
1100-8M	1104	138
1120-8M	1120	140
1128-8M	1128	141
1200-8M	1200	150
1216-8M	1216	152
1248-8M	1248	156

Section 8M

Length Code	Pitch Length-Inches	No. of Teeth
1256-8M	1256	157
1264-8M	1264	188
1272-8M	1272	159
1280-8M	1280	160
1304-8M	1304	163
1360-8M	1360	170
1392-8M	1392	174
1400-8M	1400	175
1424-8M	1424	178
1440-8M	1440	180
1456-8M	1456	182
1480-8M	1480	188
1576-8M	1576	197
1600-8M	1600	200
1648-8M	1648	206
1680-8M	1680	210
1696-8M	1696	212
1728-8M	1728	216
1760-8M	1760	220
1800-8M	1800	225
1904-8M	1904	238
1936-8M	1936	242
2000-8M	2000	250
2080-8M	2080	260
2096-8M	2096	262
2104-8M	2104	263
2136-8M	2136	267
2208-8M	2208	276
2240-8M	2240	280
2304-8M	2304	288
2400-8M	2400	300
2504-8M	2504	313
2600-8M	2600	325
2736-8M	2736	342
2800-8M	2800	350
3200-8M	3200	400

Std Wid 20,30,50,85mm

Section 14M

Length Code	Pitch Length-Inches	No. of Teeth
966-14M	966	69
1120-14M	1120	80
1190-14M	1190	85
1246-14M	1246	89
1260-14M	1260	90
1288-14M	1288	92
1400-14M	1400	100
1470-14M	1470	105
1610-14M	1610	115
1652-14M	1652	118
1750-14M	1750	125
1764-14M	1764	126
1820-14M	1820	130
1890-14M	1890	135
1960-14M	1960	140
2002-14M	2002	143
2100-14M	2100	150
2590-14M	2590	185
2800-14M	2800	200
3108-14M	3108	222
3150-14M	3150	225
3500-14M	3500	250
3850-14M	3850	275
4760-14M	4760	340

Std Wid 40,55,85,115, 170mm